

# OUTDOOR CLEANING WITH PRESSURE WASHERS

For additional information or new ideas visit [www.outdoorcleaning.com](http://www.outdoorcleaning.com)

## Winterizing and Storage

### Getting Started



Fuel Stabilizer

### 1 ADD FUEL STABILIZER

Start by adding fuel stabilizer according to the manufacturer's directions. Run the engine for two minutes to circulate the stabilizer throughout the fuel system.



Remove Water/Solution

### 2 REMOVE WATER AND CLEANING SOLUTION

Place the injection tube into a pail of clean water and run the pressure washer in low pressure mode for one to two minutes. Shut off the pressure washer and turn off the main water supply.

Point the spray gun in a safe direction and squeeze the trigger to relieve trapped pressure. Engage the trigger lock on your spray gun.



Disconnect Hose

### 3 DISCONNECT AND DRAIN

Disconnect all hoses and drain the water from the hose, spray gun, and nozzle extension. Use a rag to wipe off the hose. Store all accessories and pull recoil handle about six times. This should remove any remaining water in the pump.



Add Pump Saver

### 4 ADD PUMP SAVER™

Move pressure washer to a dry place. Make sure the pump is emptied of all remaining liquid. Always wear eye protection when using PumpSaver™. With maintenance complete, store your pressure washer and accessories in a cool, dry place.

